

Product Name: Coolant Anti –Freeze

Product Code: FREEZEN 1L 5L

Manufacturer: FlowChemuk

Country of Origin: United Kingdom



Keep your engine running smoothly year-round with this premium, ready-to-use coolant and antifreeze. Engineered for extreme temperatures, it protects against overheating in the summer and freezing in the winter. Its advanced formula also prevents corrosion and maintains optimal engine performance—ensuring long-lasting reliability in any driving condition

Key Features:

All-Season Protection : Shields your engine from both overheating in hot weather and freezing in cold climates.

Ready-to-Use Formula : Pre-mixed for convenience, no measuring or mixing required. Just pour and go.

Corrosion Prevention : Inhibits rust and corrosion to extend the life of your engine and cooling system components.

Optimized Engine Performance: Helps maintain a stable operating temperature, ensuring smooth and efficient engine function.

Versatile Compatibility : Safe for use in a wide range of vehicles gasoline, diesel, and hybrid engines alike.

Property	Specification
Appearance	Yellow Liquid
Odour	MILD
PH	NA
Freezing Point	NA
Shelf Life	2 Years (unopened)
Storage	Store in a cool, dry place, away from direct sunlight



Instructions for Use:

- Ensure Engine is Cool
- Turn off the engine and let it cool completely before opening the radiator cap or coolant reservoir to prevent burns or injury.
- Locate the Coolant Reservoir or Radiator Cap
- Refer to your vehicle's owner's manual to locate the coolant fill point. Most vehicles have a marked overflow reservoir.
- Check Coolant Level
- Inspect the coolant level. If it's below the "MIN" or "LOW" line, it's time to add coolant.
- Add Coolant
- Slowly pour the ready-to-use coolant/antifreeze into the reservoir or radiator until it reaches the "MAX" or "FULL" line. Do not overfill.
- Secure the Cap
- Tightly close the radiator cap or reservoir cap once you've topped off the coolant.
- Run the Engine
- Start the engine and let it run for a few minutes. Check for leaks and ensure the coolant circulates properly.
- Monitor Levels
- Recheck the coolant level after the engine cools again. Top off if necessary.

Health and Safety:

Consult the material safety data sheet for advice on handling and safety procedures.

- Signal word (CLP) : Warning
- Contains : ethanediol, ethylene glycol
- Hazard statements (CLP) : H302 - Harmful if swallowed.
- Precautionary statements (CLP) : P264 - Wash hands, forearms and face thoroughly after handling.
- P270 - Do not eat, drink or smoke when using this product.
- P301+P312 - IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. P330 - Rinse mouth.
- P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.



Contact Us



Sales@flowchemuk.com



www.flowchemicals.co.uk

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate. However it is given without guarantee, as conditions of use and workmanship involved are both beyond our control. All information supplied is subject to the company's terms and conditions of sale, copies of which are available on request.